

## NASCAR XF front package

---

### options

---

- 12.625"x1.375" heavy duty rotor
- 12.625"x1.375" standard rotor
- 12.625"x1.25" light weight rotor
- Fixed drive or bobbin drive hat systems.
- Front or rear mount available

### features and benefits

---

- Machined from billet aircraft aluminum alloy for superior strength at high temperatures.
- Radial mount with adaptor bracket for accurate positioning.
- Mono-block construction for increased caliper stiffness.
- Large pad area and volume for maximum braking performance and pad life.
- Light weight, hard anodized aluminum pistons.
- Ventilated piston inserts to reduce heat transfer through the brake fluid.
- Special coating in rotor pathway to reduce heat transfer to the caliper.



### specifications

---

<b>Piston size</b>	1.875" / 1.75"
<b>Pad area</b>	80.20cm <sup>2</sup> / 12.4 in <sup>2</sup>
<b>Pad volume</b>	192.5cm <sup>3</sup> / 11.7 in <sup>3</sup>
<b>Pad thickness</b>	28mm / 1.10"
<b>Standard rotor 12.625x1.375 / 48 vane</b>	19.05 lbs.
<b>Light weight rotor 12.625x1.375 / 48 vane</b>	16.73 lbs.
<b>XF front caliper</b>	7.89 lbs.
<b>Fixed drive hat</b>	2.72 lbs.
<b>Bobbin drive hat</b>	2.68 lbs.
<b>Fixed drive hardware (axle set)</b>	1.01 lbs.
<b>Bobbin drive hardware (axle set)</b>	1.21 lbs.

### applications

---

NASCAR Nextel Cup, Busch Series and Craftsman Truck Series.

# NASCAR XF front package

## CALIPERS

**XF**  
**CAR6045S01DSL & RL**




Bracket **BAA4490X600**  
 Service kit **CSK4549EB751**

## PADS


**FULL DEPTH PAD**

FERODO - FRP3059\*  
 MINTEX - 1247\*\*\*28  
 PAGID - U1220RS\*\*28  
 PFC - 7702.\*\*28.4  
 WILWOOD - 15A-5739K



**SCALLOPED PAD**

FERODO - FRP3060\*  
 MINTEX - 1797\*\*\*28  
 PAGID - PNP4448X523.4  
 PFC - 7712.\*\*28.4  
 WILWOOD - 15A-6225K




## ROTORS

12.625"x1.375"  
**DIV2135X014C48L & R**  
 12.625"x1.25"  
**DIV2135X381C48L & R**  
 12x6.75" Bolt Circle


12.625"x1.375"  
**DIV2135X364C48L & R**  
 12.625"x1.25"  
**DIV2135X402C48L & R**  
 12x7.625" Bolt Circle

## HATS


BOBBIN DRIVE  
 2.125" - **BAD2129X397**  
 2.00" - **BAD2129X537**  
 1.875" - **BAD2129X432**



FIXED DRIVE  
 2.125" - **BAD2129X517**  
 2.00" - **BAD2129X544**  
 1.875" - **BAD2129X545**



FIXED OR BOBBIN DRIVE  
 2.125" - **BAD2129X547**  
 2.00" - **BAD2129X539**  
 1.875" - **BAD2129X538**



## HARDWARE

**BBK3030X001.12**  
 Kit contains:  
 12 x BSD3430X528M  
 12 x BSS4474X672  
 12 x NSB0080X063

BOLT - **BSS4441X672**  
 NUT - **NSR3430X288**  
 (12 PER HAT)

BOBBIN DRIVE  
**BBK3625X001.12**  
 Kit contains:  
 12 x BSD3430X401M  
 12 x BSS4474X641  
 12 x NSB0080X063

FIXED DRIVE  
**BBK0621X001.12**  
 Kit contains:  
 12 x BSS4474X637  
 12 x W5F0080X114  
 12 x NSB0080X063

## Service parts

1.875" piston	<b>PSA4493X610</b>	bridge pipe	<b>PSA4460X650</b>
1.875" piston seal	<b>SES4900X751</b>	recirculator kit	<b>PSC4460X700</b>
1.75" piston	<b>PSA4493X609</b>	bleed screw	<b>FSB0080X008</b>
1.75" piston seal	<b>SES4500X751</b>	caliper temp. strips	<b>TH50080X285</b>

Updated 11/9/2004

**Alcon (Mooresville)**  
**T** +1 (704) 799 2723  
**F** +1 (704) 799 2287  
**E** jthomas@alconusa.com

